


DACO-HI LED HIGH BAY

SYLVANIA



Superior thermal management
An even heat distribution and lower temperature rise



Control Options

Add to the product part numbers to include these control options

Occupancy Control SESr
DALI Control DALI
1-10V Dimming Control 1-10V

Dimmable optional extra

Fixed surface mount
HC-CMBK



Flexible surface mount
HC-PMBK



Wall mount
HC-WMBK




Pipe mount
HC-PPBK



SPECIFICATION

- High performance SMD design
- Output options up to 24,300lm (200W)
- Efficacy up to 120lm/W
- Electrical: 100-277V~, 47-63Hz, PF≈0.95
- LED life projection >100,000 hours (TM21 L₇₀)
- Energy savings up to 90%, (depending on installation and usage patterns)
- CCT: 5000K (other °K available to special order)
- CRI>70 (CRI>80 optional)
- Standard Beam angle 120° (Optional 60°)
- Superior uniformity
- Superior temperature stability
- Temperature tested for the toughest conditions
- Quality Meanwell long life driver
- Compact size (383mm x 195mm)
- Light weight (6-7kg)
- No external reflectors required
- Tempered safety glass diffuser
- Operating range -30~+50°C
- Body : Aluminium alloy
- Stainless steel screws
- IP65 Protection rating
- 0.3m flex (other lengths and plugs optional)



Part numbers	DACO HI 100LED/5KWb	DACO HI 120LED/5KWb	DACO HI 150LED/5KWb	DACO HI 200LED/5KWb
Out put	13,000lm	15,600lm	19,500lm	26,000lm
Power	100W	120W	150W	200W
Efficacy	130lm/W			
CCT	5,000K			
CRI	>70			
Beam angle	120			
Nichia LED	112	140	189	252
Input Voltage	100-277Vac 47-63Hz Pf.0.95			
IP. Rating	IP.65			
Driver	Internal			
HID Equivalent	250W	250-400W	400-600W	700W

Alternative specification to above				
4,000K 120'	DACO HI 100LED/4KWb	DACO HI 120LED/4KWb	DACO HI 150LED/4KWb	DACO HI 200LED/4KWb
5,000K 60'	DACO HI 100LED/4KNb	DACO HI 120LED/4KNb	DACO HI 150LED/4KNb	DACO HI 200LED/4KNb
4,000K 60'	DACO HI 100LED/4KNb	DACO HI 120LED/4KNb	DACO HI 150LED/4KNb	DACO HI 200LED/4KNb

***Beam angle 50' optional extra