


DACO-MU LED HIGH BAY



**Superior thermal management**  
An even heat distribution and lower temperature rise



LED Nichia chip inside : LM-79, LM80 available

IES files : available


Certificates & Reports : TIS 1955-2551, IEC-60598, IEC 61000, IEC 62321(RoHS) and IEC 62471



TIS 1955-2551

SPECIFICATION

- High performance SMD design
- Efficacy more than 120lm/W
- Energy savings
- CRI>70 STD (CRI>80 optional)
- Superior uniformity
- Superior temperature stability
- Compact size (383mmx195mm)
- Standard beam angle 120° 90° 60°
- No external reflectors required
- Tempered safety glass diffuser
- Operating range -30° C to 50° C
- IP 65 Protection rating
- Aluminum alloy body
- Stainless steel screw and hook
- Light weight (6-7Kg)
- Recessed ring optional extra



Model	DACO MU 100LED	DACO MU 120LED	DACO MU 150LED	DACO MU 200LED
Out put (Lm)	12,000	14,400	18,000	24,000
Power (W)	100	120	150	200
Efficacy (lm/W)	120			
CCT	3,000K/4,000K/5,000K			
CRI	>73			
Beam angle	120° 90° 60°			
Life Span	50,000Hrs			
Nichia LED	112	140	189	252
Input Voltage	100-277Vac 47-63Hz Pf.0.95			
IP. Rating	IP.65			
Driver	Internal			
HID Equivalent	125-150W	150-250W	250W	250-400W
Warraatee	3 Years	3 Years	3 Years	3 Years

SYLVANIA