

JETA II LED 30-50W



JETA II LED 100-200W



SPECIFICATION

1. High light efficiency imported LED chip, the luminous flux over 90LM/W.
2. All the led floodlight's material is Die- casting Alu
3. Long lifetime, can reach 40,000 hours.
4. It could save 70% energy then the traditional light.
5. Eco-friendly, no heavy metal and harmful gas.
6. It has good weatherability, waterproof level is IP65 and the insulation class .
7. Widely used in outdoor .Park & factory & garden & hotel and so on

Model.	Power	Luminous Flux	Luminous Efficiency	Voltage	PF	CRI	Beam Angle	CCT	Protective Grade
JETA II- LED 30W	30W	2700±10%	90lm/W±10	AC180-240V/50-60Hz	≥0.9	≥80	120°	3000	IP65
JETA II- LED 30W	30W	2700±10%	90lm/W±10	AC180-240V/50-60Hz	≥0.9	≥80	120°	6500	IP65
JETA II- LED 50W	50W	4500±10%	90lm/W±10	AC180-240V/50-60Hz	≥0.9	≥80	120°	3000	IP65
JETA II- LED 50W	50W	4500±10%	90lm/W±10	AC180-240V/50-60Hz	≥0.9	≥80	120°	6500	IP65
JETA II- LED 100W	100W	9000±10%	90lm/W±10	AC180-240V/50-60Hz	≥0.9	≥70	120°	3000	IP65
JETA II- LED 100W	100W	9000±10%	90lm/W±10	AC180-240V/50-60Hz	≥0.9	≥70	120°	6500	IP65
JETA II- LED 200W	200W	18000±10%	90lm/W±10	AC180-240V/50-60Hz	≥0.9	≥70	120°	6500	IP65