

Product datasheet

Specifications



APC Smart-UPS, Line Interactive, 1000VA, Rackmount 2U, 230V, 4x IEC C13 outlets, SmartConnect Port+SmartSlot, AVR, LCD

SMT1000RMI2UC

Overview

Presentation Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

Lead time Usually in Stock

Main

Main Input Voltage 230 V

Other Input Voltage 220 V
240 V

Main Output Voltage 230 V

Other Output Voltage 220 V
240 V

Rated power in W 700 W

Rated power in VA 1000 VA

Product or component type Uninterruptible power supply (UPS)

Input Connection Type IEC 320 C14

output connection type 4 IEC 320 C13
2 IEC Jumpers

Number of rack unit 2U

Number of cables 1

Battery type Lead-acid battery

Provided equipment Documentation CD
Installation guide
Rack mounting support rails
USB cable

Range of product Smart-UPS

Complementary

Communication port type SmartConnect Ethernet port
SmartSlot


Software package SmartConnect software for remote power monitoring feature availability varies by terms of use

Batteries & Runtime

Run Time [View Runtime Graph](#)

Efficiency [View Efficiency Graph](#)

Additional information Configurable for 220 : 230 or 240 nominal output voltage

Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery life	4...6 year(s)
Replacement battery	APCRBC157 
Battery charger power	112 W rated

General

Number of power module	0
Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	Cloud-enabled monitoring
Redundant	No

Physical

Colour	Black
Height	8.6 cm
Width	43.2 cm
Depth	47.7 cm
Product weight	22.5 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	Yes

Input

Input voltage limits	151...302 V adjustable 160...286 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Harmonic distortion	Less than 5 %
Maximum configurable power in VA	1000 VA
Maximum configurable power in W	700 W
Transfer time	6 ms typical : 10 ms maximum
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Conformance

Product certifications	CSA EAC RCM VDE UK PSTI
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Acoustic level	45 dBA
Heat dissipation	56 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.0000000000...15240.0000000000 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

Communications & Management

control panel	Multifunction LCD status and control console
Emergency power off	Optional
Free slots	1
Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rate	459 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.095 cm
Package 1 Width	59.385 cm
Package 1 Length	60.325 cm
Package 1 Weight	30.000 kg
Unit Type of Package 2	P12
Number of Units in Package 2	4
Package 2 Height	75.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	132.000 kg

Contractual warranty

Warranty

3 years repair or replace (excluding battery) and 2 years for battery

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[How this information helps you](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	1165
--	-------------

Environmental Disclosure	Product Environmental Profile
--------------------------	---

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
--	-----------

Packaging without single use plastic	No
--------------------------------------	-----------

EU RoHS Directive	Compliant with Exemptions
-------------------	----------------------------------

SCIP Number	B2b22a56-41f2-497e-9ea6-cf093b3b8bd3
-------------	---

REACH Regulation	REACH Declaration
------------------	-----------------------------------

Energy efficiency

Optimized Energy Efficiency	Energy efficient product
-----------------------------	---------------------------------

Use Again

Repack and remanufacture

Circularity Profile	End of Life Information
---------------------	---

Removable battery

User replaceable

Take-back

Yes

Image of product / Alternate images

Alternative





