

GPSA-A/U


spool



ref.	item	D/d (mm)	spool length (m)	min./mult. ord. qty (m)	Allowed busbar size	
					A+B (mm) min – max	C (mm) min – max
GP1025	GPSA-25/10-A/U	25/10	25	25	17 – 28	11 – 20
GP1040	GPSA-40/16-A/U	40/16	20	20	28 – 45	18 – 32
GP1065	GPSA-65/25-A/U	65/25	15	15	44 – 69	28 – 47
GP1100	GPSA-100/40-A/U	100/40	15	15	69 – 102	44 – 72
GP1150	GPSA-150/60-A/U	150/60	15	15	102 – 148	65 – 105
GP1175	GPSA-175/80-A/U	175/80	10	10	133 – 196	85 – 125

GPSA-1000

1 meter bars



ref.	item	D/d (mm)	length (m)	min./mult. ord. qty (m)	Allowed busbar size	
					A+B (mm) min – max	C (mm) min – max
GP3025	GPSA-25/10-1000	25/10	1	1	17 – 28	11 – 20
GP3040	GPSA-40/16-1000	40/16	1	1	28 – 45	18 – 32
GP3065	GPSA-65/25-1000	65/25	1	1	44 – 69	28 – 47
GP3100	GPSA-100/40-1000	100/40	1	1	69 – 102	44 – 72
GP3150	GPSA-150/60-1000	150/60	1	1	102 – 148	65 – 105
GP3175	GPSA-175/80-1000	175/80	1	1	133 – 196	85 – 125



D Diameter before shrinkage
d Diameter after free shrinkage

- A Rectangular busbar longer side
- B Rectangular busbar shorter side
- C Round busbar diameter